



MINO 40

suspended

EN Luminaire housing from extruded aluminium profile, angular design; no visible screws; surface powder coated; luminaire profile can be pre-mounted; remaining luminaire components mounted without tools; pendant fitting with cable suspension; height adjustment without tools; incl. transparent feed; light inset consisting of highly reflective coated extruded profile for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering


DE Leuchtenkörper aus Aluminiumstrangpressprofil, kantige Ausführung; keine sichtbaren Schrauben; Oberfläche pulverbeschichtet; Leuchtenprofil vorab montierbar; restliche Leuchtenkomponenten werkzeuglos montierbar; abgependelt mit Seilabhängung; werkzeuglose Höhenverstellung; inkl. transparenter Einspeiseleitung; Lichteinsatz bestehend aus hochreflektierend lackiertem Strangpressprofil für verbessertes Thermomanagement; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; energieeffiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

3000 K, 4000 K
 CRI ≥ 90, 3 SDCM
 up to 116 lm/W
 L90 @ 50 000 h
 DALI-2
 opal

Types

suspended



Colours




Light distribution




direct




DiiA® standards
 251, 252, 253



system
 solution (p. 912)



tunable white
 2700–6500 K



CRI ≥ 98
 XPECTRUM

Order options

COLOUR TEMPERATURE	☑☑
3000K	0
4000K	1

CONTROL	
DALI-2	

MATERIAL COLOUR	☑
○ pure white RAL 9010	7
○ traffic white RAL 9016	W
● white aluminium RAL 9006	G
● jet black RAL 9005	8


LIGHT OPTIC COVER	
opal high performance	

Options on request

COLOUR RENDERING INDEX	
CRI ≥ 98 XPECTRUM	

COLOUR TEMPERATURE	
tunable white 2700–6500K	
DALI-2 DT8	

LIGHT OPTIC COVER	
microprismatic	



MINO 40 suspended



MID LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
12.4W	3000K	1370lm	1008	0 4 2 - 1 2 1 2 :: 3 ☑ H
	4000K	1430lm		
24.8W	3000K	2730lm	2008	0 4 2 - 1 2 1 4 :: 3 ☑ H
	4000K	2860lm		
37W	3000K	4100lm	3008	0 4 2 - 1 2 1 6 :: 3 ☑ H
	4000K	4300lm		

HIGH LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
20.1W	3000K	2140lm	1008	0 4 2 - 1 2 2 2 :: 3 ☑ H
	4000K	2240lm		
40W	3000K	4270lm	2008	0 4 2 - 1 2 2 4 :: 3 ☑ H
	4000K	4470lm		
60W	3000K	6410lm	3008	0 4 2 - 1 2 2 6 :: 3 ☑ H
	4000K	6710lm		